



が、後の

MICROCOPY RESOLUTION TEST CHART MATIONAL BUREAU OF STANDARDS-1963-A

7

FTD-ID(RS)T-0616-84

FOREIGN TECHNOLOGY DIVISION



SOLAR CELLS

OTIC FILE COPY

AD-A142 087



SELECTE JUN 15 1984 S

D

Approved for public release; distribution unlimited.

84 06 14 048

EDITED TRANSLATION

FTD-ID(RS)T-0616-84

31 May 1984

MICROFICHE NR: FTD-84-C-000554

SOLAR CELLS

English pages: |

Source: Mechanik, Nr. 8, 1978, pp. 448

Country of origin: Poland

Translated by: LEO KANNER ASSOCIATES

F33657-81-D-0264

Requester: FTD/TQTD

Approved for public release; distribution unlimited.

NTIS GRA&I DTIC TAB Un manounced Justification. Ву .____ Distribution/ Availability Codes Avail and/or D15t Special

THIS TRANSLATION IS A RENDITION OF THE ORIGI-NAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DI-VISION.

PREPARED BY:

TRANSLATION DIVISION FOREIGN TECHNOLOGY DIVISION WP-AFB, OHIO.



GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc. merged into this translation were extracted from the best quality copy available.

SOLAR CELLS

Solar cells--photoelectric generators--are devices in which the energy of solar radiation is converted into electrical energy. The most diffuse and the only one suited for industry is the silicon cell. The application of semiconductor material has allowed an output amouting to 13.5 percent to be achieved. These cells are used mainly in astronautical technology.

The best properties are possessed by generators with structures using GaAs (gallium-arsenic) material. Their output amounts to 17.5 percent. In this respect, gallium-arsenic cells will be better suited for solar powerplants than silicon, which cannot operate at temperatures exceeding 150oC.